

Authoritative Restore

Hvad er det

Tillader administratoren at recover en domain controller, restore den til et bestemt tidspunkt, eller markere objekter i AD til at være authoritative

Authoritative betydning

"For example, you might need to perform an authoritative restore if an administrator inadvertently deletes an organizational unit containing a large number of users. If you restore the server from tape, the normal replication process would not restore the inadvertently deleted organizational unit. Authoritative restore allows you to mark the organizational unit as authoritative and force the replication process to restore it to all of the other domain controllers in the domain."

Kommandoer

`Restore database`

"Marks the entire Ntds.dit (both the domain and configuration naming contexts held by the domain controller) as authoritative. The schema cannot be authoritatively restored."

`Restore database verinc %d`

Marks the entire Ntds.dit (both the domain and configuration naming contexts held by the domain controller) as authoritative and increments the version number by % d . Use this option only to authoritatively restore over a previous, incorrect, authoritative restore, such as an authoritative restore from a backup that contains the problem you want to restore over.

Authoritative Restore (cont)

`Restore subtree %s`

"Marks subtree (and all children of subtree) as being authoritative. The subtree is defined by using the fully distinguished name of the object."

`Restore subtree %s verinc %d`

Marks subtree (and all children of subtree) as being authoritative and increments the version number by % d . The subtree is defined by using the fully distinguished name of the object. Use this option only to authoritatively restore over a previous, incorrect, authoritative restore, such as an authoritative restore from a backup that contains the problem you want to restore over.

Source

<https://technet.microsoft.com/en-us/library/cc940334.aspx>

Tombstone Lifetime

Hvad er det

Tombstone Lifetimen i en AD forest bestemmer hvor lang tid et slettet object (en tombstone) er i

Se tombstone lifetime med Dsquery

Åben kommandoprompten og skriv `dsquery * " cn= directory service,cn=windows nt est DN" -scope base -attr tombstone lifetime` Skift <forestDN> ud med navn

Source

[https://technet.microsoft.com/en-us/library/cc784932\(v=ws.10\).aspx](https://technet.microsoft.com/en-us/library/cc784932(v=ws.10).aspx)

DSRM - Directory Services Restore Mode

Hvad er det

DSRM er en speciel boot mode for reparation

Syntax

`dsrm <ObjectDN> ... [-subtree [-uco | -uci]]`

Boot ind i DSRM

For at boote ind i Directory Services Restore Mode eller DS Restore Mode

Log ind i DSRM

Efter du er bootet op i DSRM så log ind med

Boot ind i DSRM genvej inde fra windows

`bcdedit /set safeboot dsrepair, th`

Source

<https://u-tools.com/help/DSRM.asp>

[https://technet.microsoft.com/en-us/library/cc784932\(v=ws.10\).aspx](https://technet.microsoft.com/en-us/library/cc784932(v=ws.10).aspx)



By [andreolsen4200](#)

cheatography.com/andreolsen4200/

Published 13th November, 2015.

Last updated 13th May, 2016.

Page 1 of 2.

Sponsored by [CrosswordCheats.com](#)

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

cheatography.com/andreolsen4200/