

Basic Methods	
imp→	import moduleName from 'module'
imn→	import 'module'
imd→	import { destructuredModule } from 'module'
ime→	import * as alias from 'module'
ima→	import { originalName as aliasName } from 'module'
exp→	export default moduleName
exd→	export { destructuredModule } from 'module'
exa→	export { originalName as aliasName } from 'module'
enf→	export const functionName = (params) => { }
edf→	export default (params) => { }
met→	methodName = (params) => { }
fre→	arrayName.forEach(element => { }
fof→	for(let itemName of objectName { }
fin→	for(let itemName in objectName { }
anfn→	(params) => { }
nfn→	const functionName = (params) => { }
dob→	const {propName} = objectToDe- escruct
dar→	const [propName] = arrayToDe- scruct
sti→	setInterval(() => { }, intervalTime
sto→	setTimeout(() => { }, delayTime
prom→	return new Promise((resolve, reject) => { }
cmmb→	comment block
cp→	const { } = this.props
cs→	const { } = this.state
Others	
cmmb→	comment block
React	
imr→	import React from 'react'
imrd→	import ReactDOM from 'react- dom'
imrc→	import React, { Component } from 'react'
imrcp→	import React, { Component } from 'react' & import PropTypes from 'prop-types'
imrpc→	import React, { PureComponent } from 'react'
imrpcp→	import React, { PureComponent } from 'react' & import PropTypes from 'prop-types'
imrm→	import React, { memo } from 'react'
imrmp→	import React, { memo } from 'react' & import PropTypes from 'prop-types'
impt→	import PropTypes from 'prop-- types'
imrr→	import { BrowserRouter as Router, Route, Link } from 'react-router-dom'
redux→	import { connect } from 'react- redux'
rconst→	constructor(props) with this.state
rconc→	constructor(props, context) with this.state
est→	this.state = { }
cwm→	componentWillMount = () => { } DEPRECATED!!!
cdm→	componentDidMount = () => { }
cwr→	componentWillReceiveProps = (nextProps) => { } DEPREC- ATED!!!
scu→	shouldComponentUpdate = (nextProps, nextState) => { }
React (cont)	
cwup→	componentWillUpdate = (nextProps, nextState) => { } DEPRECATED!!!
cdup→	componentDidUpdate = (prevP- rops, prevState) => { }
cwun→	componentWillUnmount = () => { }
gdsfp→	static getDerivedStateFromPr- ops(nextProps, prevState) { }
gsbu→	getSnapshotBeforeUpdate = (prevProps, prevState) => { }
ren→	render() { return() }
sst→	this.setState({ })
ssf→	this.setState((state, props) => return { })
props→	this.props.propName
state→	this.state.stateName
rcontext→	const \${1:contextName} = React.createContext()
cref→	this.\${1:refName}Ref = React.createRef()
fref→	const ref = React.createRef()
bnd→	this.methodName = this.meth- odName.bind(this)
Redux	
rxaction→	redux action template
rxconst→	export const \$1 = '\$1'
rxreducer→	redux reducer template
rxselect→	redux selector template
Console	
clg→	console.log(object)
clo→	console.log("object", object)
ctm→	console.time("timelid")
cte→	console.timeEnd("timelid")
cas→	console.assert(expression,object)
ccl→	console.clear()
cco→	console.count(label)
cdi→	console.dir
cer→	console.error(object)



Console (cont)

cgr→	console.group(label)
cge→	console.groupEnd()
ctr→	console.trace(object)
cwa→	console.warn
cin→	console.info

Component Templates

rfc	react functional component
rfce	react functional component with last line export
rfcp	react functional component with PropTypes and last line export
rcc	react class component
rce	react class component with last line export
rccp	react class component with PropTypes and ES7 module system
rcep	react class component with PropTypes and last line export
rcredux	redux connected class component with PropTypes
reduxmap	mapping to props constants
rpc	react pure component
rpcp	react pure component with PropTypes
rpce	react pure component with PropTypes and last line export
hoc	react higher order component with PropTypes
hocredux	redux connected higher order component with PropTypes
rafc	react arrow function component



By [frankieali4](#)
cheatography.com/frankieali4/

Published 19th February, 2019.
Last updated 19th February, 2019.
Page 2 of 2.

Sponsored by [Readable.com](#)
Measure your website readability!
<https://readable.com>