

Glossary

pod	Group of containers that are deployed together on the same host
service	Abstraction which defines a logical set of pods and a policy by which to access them
node	Worker machine in the cluster
configmap	Public configuration data in the form of a key-value pair
secret	Private configuration data
job	Creates pod(s) and ensures that a specified number successfully terminate
cronjob	Time-based job
ingress	API object that manages external access to the services in a cluster, typically HTTP.
deployment	Desired state of pods for declarative updates
daemonset	Specification that requires a particular pod to be run on some or all nodes
replicaset	Requirement that a specified number of pods are running at any given time
persisten-tvolume	Persistent storage in the cluster with an independent lifecycle
persistentvo-lumeclaim	Request for storage (for a Persis ten tVolume) by a user

Cluster Management

```
kubect1 proxy
```

```
kubect1 port-f orward {pod_name} {local _port}: {remote _port}
```

```
kubect1 scale --repl icas=3 {resou rce _ty pe} /{r eso urc e_name }
```

Viewing Objects

```
kubect1 get --all- nam espaces {objec t_type}
```

```
kubect1 describe {objec t_type}
```

```
kubect1 get services --sort -by =.m eta dat a.name
```

```
kubect1 get pods --fiel d-s ele cto r=s tat us.p ha s = Running
```

```
kubect1 get events
```

Modifying Objects

```
kubect1 proxy
```

Proxy the api server API to your local machine on port 8001

```
kubect1 port-f orward {pod_name} {local _port}: {remote _port}
```

Forward the pod port to your local port

```
kubect1 scale --repl icas=3 {resou rce _ty pe} /{r eso urc e_name }
```

Scale given resource

<code>kubect1 apply -f ./myma nif est.yaml</code>	Apply a configuration to a object by filename or stdin. Also overrides the existing configuration.
<code>kubect1 create -f ./myma nif est.yaml</code>	Create object(s)
<code>kubect1 create -f ./dir</code>	Create object(s) in all manifest files in dir
<code>kubect1 create -f https://g it.i o/vPi eo</code>	Create from url
<code>kubect1 run nginx --imag e=nginx</code>	Start a single instance of nginx
<code>kubect1 replace -- force -f ./pod.json</code>	Force replace, delete and then re-create the resource. Will cause a service outage.
<code>kubect1 edit svc/do cke rre gistry</code>	Edit the service named docker-re-gistry



By **jwilkinson**
cheatography.com/jwilkinson/

Published 9th March, 2018.
 Last updated 9th March, 2018.
 Page 1 of 2.

Sponsored by **ApolloPad.com**
 Everyone has a novel in them. Finish Yours!
<https://apollopadd.com>