

ssh		Statements (cont)	
sshfs [USER@ HOST]: [remote_directory] mountpoint	mount -t sshfs [remote_directory] mountpoint	mount -t sshfs [remote_directory] mountpoint	same different syntax
ssh -o ServerAliveInterval=X -o ServerAliveCountMax=Y [HOST]	ssh -o ServerAliveInterval=X -o ServerAliveCountMax=Y [HOST]	ssh -o ServerAliveInterval=X -o ServerAliveCountMax=Y [HOST]	Maintaing ssh conection for X seconds and Y tries
ssh-copy-id -i ~/.ssh/id_rsa [USER@ HOST]	ssh-copy-id -i ~/.ssh/id_rsa [USER@ HOST]	ssh-copy-id -i ~/.ssh/id_rsa [USER@ HOST]	add autentication via ssh, not .pub file
autossh -N -f -L localhost:[PORT]:localhost:[PORT] [USER@ HOST]	autossh -N -f -L localhost:[PORT]:localhost:[PORT] [USER@ HOST]	autossh -N -f -L localhost:[PORT]:localhost:[PORT] [USER@ HOST]	map local port to PORT on USER@HOST with autore-connect
operations on files & drives		system	
cp -r \$(file _list ed.txt) outdir	cp -r \$(file _list ed.txt) outdir	uname -a	copies files & directories listed in file _list ed.txt to outdir
xargs -a file_list ed.txt cp -r -t outdir	xargs -a file_list ed.txt cp -r -t outdir	ss -tpln	same as above
tar -(v)czf file.tar.gz /path/ to_compress	tar -(v)czf file.tar.gz /path/ to_compress	lsblk -S	create -cf archive -xf for extract
unzip file.zip -d file	unzip file.zip -d file	dd if=/path/to/image.iso of=/drive/lo	unzip file.zip to file directory (must exists before)
mkdir -p dir	mkdir -p dir	cp bs=4M && sync	make parent directories as needed, no error
rm -r !(*.ext)	rm -r !(*.ext)	sudo mount [drive] [mount point]	delete everything except files with extension .ext
du -hs dir	du -hs dir	du -s \$(pgrep -f [pattern])	check size of dir use -9 for GB or -m for MB
basename path/basename.ext .ext	basename path/basename.ext .ext	path without env	get basename from path without env
grep -i -r -E 'pattern1 pattern2 pattern3'	grep -i -r -E 'pattern1 pattern2 pattern3'	multiple patterns with grep -i case insensitive -r recursive	multiple patterns with grep -i case insensitive -r recursive
find PATH -(iname "pattern" -type d/f	find PATH -(iname "pattern" -type d/f	list files or directories with matching pattern in specified PATH	list files or directories with matching pattern in specified PATH

Statements		
	<code>git rm -r --cached <pa th/ fil e.e</code>	remove untracked files
<code>while read line; do [Command] done < input.file</code>	Loop over file content	
	<code>git clean -d -n/f)</code>	remove undone changes add: -n
<code>for file in ./*.ex ten tion; do [Command] done</code>	loop over files in directory	to show files to remove or -f to remove them
	<code>git fetch --all [branc h_name]</code>	copies all changes from last pull/clone on current branch or given branch name
<code>if test -f file.txt; then [Command] fi</code>	check if file exists -f, -d	
	for directory	<code>git log --not --remotes</code> all commits on all branches that aren't pushed yet
		<code>git checkout -b <ne w_b ran ch></code> change & create new branch
		<code>git switch -c <ne w_b ran ch></code> same as above



By **Kamil** (Kamil)
cheatography.com/kamil/

Published 20th July, 2021.
 Last updated 20th December, 2022.
 Page 1 of 2.

Sponsored by **CrosswordCheats.com**
 Learn to solve cryptic crosswords!
<http://crosswordcheats.com>