

Rows - Grid System

Rows are in `.container` or `.container-fluid`

Columns

<code>.col-xs-</code>	Always	Full
<code>.col-sm-</code>	>768	750 wide
<code>.col-md-</code>	>992	970 wide
<code>.col-lg-</code>	>1200	1170 wide

Resets, Offsets, Pushes, Pulls

`.clearfix`

`.col-xs-offset- (sm, md, lg)`

Nest using a .row inside a col

`.col-xs-push- (sm, md, lg)`

`.col-xs-pull- (sm, md, lg)`

`.visible-xs (sm, md, lg)`

`.hidden-xs (sm, md, lg)`

`.visible-print`

`.hidden-print`

Grid Variables

<code>@grid-columns:</code>	12
<code>@grid-gutter-width:</code>	30px
<code>@grid-float-breakpoint:</code>	768px

Using Grid Mixin CSS

```
.wrapper { .make-row(); }
.content-main { .make-lg-column(8); }
.content-secondary {
  .make-lg-column(3);
  .make-lg-column-offset(1);
}
```

Using Grid Mixin HTML

```
<div class="wrapper">
  <div class="content-main">...</div>
  <div class="content-secondary">...</div>
</div>
```

Typography

<code>.h1</code>	<code>.h2</code>	<code>.h3</code>
<code>.h4</code>	<code>.h5</code>	<code>.h6</code>
<code>.small</code>	<code><small></code>	<code>.lead</code>

`@font-size-base` | `@line-height-base`

Align

<code>.text-left</code>	<code>.text-right</code>
<code>.text-center</code>	<code>.text-justify</code>

Text Helpers

<code>.text-muted</code>	<code>.text-primary</code>
<code>.text-success</code>	<code>.text-info</code>
<code>.text-warning</code>	<code>.text-danger</code>
<code>.bg-primary</code>	<code>.bg-success</code>
<code>.bg-info</code>	<code>.bg-warning</code>
<code>.bg-danger</code>	
<code>.text-hide</code>	<code>.sr-only</code>

Lists

<code>.list-unstyled</code>	<code>.list-inline</code>
-----------------------------	---------------------------

Descriptions

```
<dl> <dt>...</dt> <dd>...</dd> </dl>
.dl-horizontal
```

Images

<code>.img-responsive</code> (max-width:100%, height:auto)
<code>.img-rounded</code>
<code>.img-circle</code>
<code>.img-thumbnail</code> (double border)

Forms

NEED TO DO

Buttons

```
<button type="button" class="btn btn-default">Default</button>
<a href="#" class="btn btn-primary btn-lg active" role="button">Primary link</a>
```

Button Classes

<code>.btn-default</code>	<code>.btn-primary</code>
<code>.btn-success</code>	<code>.btn-info</code>
<code>.btn-warning</code>	<code>.btn-danger</code>
<code>.btn-link</code> (to look like a link)	
<code>.btn-lg</code>	<code>.btn-sm</code>
<code>.btn-xs</code>	<code>.btn-block</code>
<code>.active</code> (A tag)	<code>.disabled</code> (A tag)
<code>disabled="disabled"</code>	

Labels


<code>.label</code>	<code>.label-default</code>
primary, success, info, warning, danger	
<code>New</code>	

Badge

`<span class="badge">42</span>`

Alerts

<code>.alert</code> <code>.alert-success</code>
success, info, warning, or danger
<code>.alert-dismissible</code>
<code><button type="button" class="close" data-dismiss="alert" aria-hidden="true">&times;</button></code>
<code>...</code>



By **John Mason** (masonjo)
cheatography.com/masonjo/
www.e-rehab.com

Published 29th April, 2014.
 Last updated 11th May, 2016.
 Page 1 of 3.

Sponsored by **Readable.com**
 Measure your website readability!
<https://readable.com>

Tables

`.table` `.table-striped`

`.table-bordered` `.table-hover`

`.table-condensed`

`.table-responsive`

Wrap `.table` in `.table-responsive`

```
<div class='table-responsive'>
```

```
...table
```

```
</div>
```

Rows or Cells

`.active` `.success` `.info`

`.warning` `.danger`

Tags

Tags (cont)

Clear Floats

`.clearfix`

Center Block (*mixin also*)

`.center-block` (`display:block`, `margin`
`auto`) | `.center-block()`;

Show (*mixin also*)

`.show` | `.show()`;

Hide (*mixin also*)

`.hide` | `.hide()`;

Glyphicons

```
<span class="glyphicon glyphicon-search"></span>
```

abbr

```
<abbr title="attribute">attr</abbr>
```

address

```
<address> <strong>Twitter, Inc.</strong>
<br> 795 Folsom Ave, Suite 600<br>
San Francisco, CA 94107<br> <abbr
title="Phone">P:</abbr> (123) 456-7890
</address>
```

blockquote

```
<blockquote> <p>Lorem ipsum dolor sit
amet, consectetur adipiscing elit. Intege-
r</p> </blockquote>
```

blockquote footer

```
<footer>Someone famous in <cite title="-
Source Title">Source Title</cite></foot-
er>
```

blockquote right justify

```
.blockquote-reverse
```

code

```
<code>&lt;section&gt;</code>
```

kbd Keyboard Entry

```
<kbd>cd</kbd>
```

.pre-scrollable

Max Height 350px box, with y-axis scrollbar. Used with **pre** tag

close button

```
<button type="button" class="close" aria-
hidden="true">&times;</button>
```

Caret

```
<span class="caret"></span>
```

Floats

```
.pull-left .pull-right
```

Float Mixin

```
.element { .pull-left(); }
```



By **John Mason** (masonjo)
cheatography.com/masonjo/
www.e-rehab.com

Published 29th April, 2014.
Last updated 11th May, 2016.
Page 2 of 3.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>