

Basic Operators

+	Addition
-	Subtraction
*	Multiplication
/	Division
=	Assign to Variable/Set equal to
%	Modulus (Int representation of remainder)
++var	increase before evaluation
var++	increase after evaluation
condition ? result : alternative;	short form of if-like structure

Input/Output

Cin	cin >> number;
Cout	cout << "Enter an integer: ";

Legal C++ Identifiers (The Rules for Var Names)

- Consists of letters (A-Z, Upper and Lowercase)
- Digits (NO DECIMALS)
- Underscores
- No Special Characters or Spaces
- No C++ Keywords by itself
- Must be Unique within it's namespace
- Case Sensitive

Example Switch Case

```
switch (operation) {
case 0:
// Things
break;
case 1:
// Things
break;
case 2:
// Things
break;
```

Example Switch Case (cont)

```
> default:
// Things
break;
}
```

Operation must be an Int, Char, or Boolean. Case: must reflect that datatype.

Example If Else

```
if ( conditional ) {
// do something
}
else if ( another conditional ) {
// do something else
}
else {
// do something as default
}
```

Example For Sentence

```
for ( init; test; command ) {
// do something
}
```

"break;" and "continue;" identical effects.

Example Do While Sentence

```
do {
//do something
} while (bool expression);
```

Pointers

int *ptr;	Pointer definition
ptr = &var1;	ptr set to address of var1
var2 = *ptr;	set var2 to value of var1



By Jeevan (sukablukagyat)

Published 18th March, 2024.

Last updated 1st May, 2024.

Page 1 of 3.

Sponsored by [CrosswordCheats.com](https://crosswordcheats.com)

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Struct Example

```
// Declare Structure
struct Order {
    int modelNumber;
    string phone;
    float cost;
};

// Main Function, define the structure variable
int main( ) {
    Order item1;
    // Give values to structure variables
    item1.modelNumber = 10;
    item1.phone = "Samsung Galaxy S";
    item1.cost = 1099.99;
    // Display/Output structure members
    cout << "Order, " << item1.phone <<
    item1.modelNumber;
    cout << "This item costs: $" << item1.cost
    << endl;
}
// Output:
// Order, Samsung Galaxy S10
// This item costs: $1099.99
```

Boolean Logic

==	Test of Equality
!=	Test of Non-Equality
<	Less Than
>	Greater Than
<=	Less Than or Equal
>=	Greater Than or Equal
!	NOT
&&	AND
	OR

Boolean expressions in C++ are evaluated left-to-right!

Data Types

int	3
float	3.0f
double	3.0
char	'a'
string	"Hello World!"
bool	true/false

File Input / Output

```
#include <fstream.h>
ifstream file; //read buffer
ofstream file; //write buffer
file.open ("filename", [file mode constant]);
//Test if the file was created
if(fs.is_open()) if(fs)
//Reads/Writes like cin and cout
file >> var; //Read
file << "Text: " << var << endl; //Write
//Read Entire line
getline (file, String);
//Read until it arrives at the end of file
while( file.eof())
//Detect if the read/write fail
if(file.fail())
//Close File
file.close();
```

Procedures

```
//Declaration
void Procedure Name()
{
    // do something
}
//Call to procedure
Procedure Name();
```

In the procedures we don't receive variables and don't return other variable.



By Jeevan (sukablukagyat)

Published 18th March, 2024.
Last updated 1st May, 2024.
Page 2 of 3.

Sponsored by [CrosswordCheats.com](https://crosswordcheats.com)
Learn to solve cryptic crosswords!
[http://crosswordcheats.com](https://crosswordcheats.com)

Functions

```
//Declaration
[returnType] functionName ( [input1Type
input1 Name, input2Type input2 Name, ...] )
{
    // do something
    return value; // value must be of type
returnType
}
//Call to function
[returnType var =] functionName ([input1Type
input1 Name, input2Type input2 Name, ...])
```

We have two methods to create and call functions:
passed with values and passed for reference.

Pass by reference: we put & before variable in the declaration.

ReturnType must be a Datatype

Cannot return more than one thing

Dynamic Array Template

```
dataType *nameOfTheDynamicArray;
nameOf The DynamicArray = new dataType[ number of elements];
nameOf The DynamicArray[0] = value;
delete [] nameOf The DynamicArray;
```

"new" function allows dynamic array to change its size, since they are parameters.

"delete" will delete everything stored in the dynamic array.

enum example

```
enum gasType {gas, diesel};
gasType gasT;
```



By Jeevan (sukablukagyat)

Published 18th March, 2024.

Last updated 1st May, 2024.

Page 3 of 3.

cheatography.com/sukablukagyat/

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>